

- Perfect as a backup power source for larger homes or a dependable source of portable power
- 9,500 running watts, 12,500 peak watts (gasoline); 8500 running watts, 11,200 peak watts (propane)
- Runs for up to 12 hours on a 6.6 gal. fuel tank with built-in fuel gauge; up to 7 hours on a 20 lb. propane tank
- Powered by a heavy duty 457cc 4-Stroke OHV Westinghouse Engine constructed with a durable cast iron sleeve
- Push-Button Electric Start pairs with key fob and is backed by emergency recoil start
- Dual fuel operation easily switches from gas to propane without shutting off unit
- Weighing 211 lb. with as low as 74 dBA operating volume
- (2) GFCI 5-20R household duplex outlets, (1) Transfer Switch Ready L14-30R 120/240-Volt twist-lock, and (1) 120/240V 14-50R with rubber outlet covers
- VFT display gives you real time updates with the voltage output, frequency, and lifetime hours
- All Westinghouse portable generators are functionally tested in the factory and may contain minimum residual oil and/or fuel odor

**Gasoline Peak Watts**

12500

**Gasoline Running Watts**

9500

**Propane Peak Watts**

11200

**Propane Running Watts**

8500

**Gasoline Peak Amps**

52A - 240V

104A - 120V

**Gasoline Running Amps**

39.5A - 240V

79A - 120V

**Propane Peak Amps**

47A - 240V

93A - 120V

**Propane Running Amps**

35A - 240V

71A - 120V

**AC Voltage**

120/240V

**AC Frequency**

60 Hz

**Outlets**

2 Duplex 120V 5-20R

1 120/240V L14-30R

1 120/240V 14-50R

ST Switch

**Total Harmonic Distortion**

≤23%

**GFCI Outlets**

Yes

**Outlet Covers**

Yes

**Transfer Switch Ready**

Yes

**RV Ready**

Yes

**ST Switch Ready**

Yes

**Display Type**

Digital Readout

**Noise Level**

74 dBA

**Fuel Gauge**

Yes

**Fuel Tank Capacity**

6.6 gal. (25 L)

**Gasoline Run Time @ 25%**

12 hrs.

**Gasoline Run Time @ 50%**

8 hrs.

**Propane Run Time @ 50%**

7 hrs.

**Starter Type**

Electric, Remote, Recoil

**Choke Type**

Automatic

**Engine Displacement**

457cc

**Engine Type**

OHV 4 Stroke

**Oil Capacity**

37.2 oz. (1.1 qt.)

**Engine Oil Type**

10W30

**Automatic Low Oil Shutdown**

Yes

**Carbon Monoxide (CO) Sensor**

No

**Overload Protection**

Yes

**CARB Compliant**

Yes

**Grounding System**

Bonded Neutral

**Battery Included**

Yes

**Included Accessories**

Oil Bottle, Oil Funnel, Spark Plug Wrench, Remote, Propane Regulator/Hose, Battery Float Charger

**Warranty (Residential)**

3 Year Limited

**Warranty (Commercial)**

1 Year Limited

**Product Dimensions**

27.2L x 26.1W x 26.5H in.

**Dry Unit Weight**

211 lb. (95.7 kg)

**Packaging Dimensions**

31L x 21.5W x 23H in.

**Shipping Weight**

226 lb. (102.5 kg)

**UPC**

853544008298